


PIN ASSIGNMENT

P1	P2	P3	P4
1	白 White	1	
2	紅 Red	1	
3	黃 Yellow		1
4	GND	2	GND 2



NOTE;

1.100% TEST OPEN SHORT&MISWIRE;

2.INSULATION RESISANCE:1M ohm(MIN)

3.繞線方式請見右圖:單條包裝.50PCS/袋.貼數量標籤

"50PCS"與環保標籤.用"04"環保膠袋.



7	MOLDING	P4:50P PVC 膠料 黃色-6 Yellow	6g
6	MOLDING	P3:50P PVC 膠料 白色-1 White	6g
5	MOLDING	P2:50P PVC 膠料 紅色-3 Red	6g
4	MOLDING	P1:50P PVC 膠料 黑色 Black	6g
3	CONNECTOR	3.5四極頭 鍍鎳 3.5mm Male Nickle Plated	1pc
2	CONNECTOR	RCA公,鍍鎳(梅花一體式) RCA-Male Nickle Plated	3pcs
1	CABLE	NDU-UL26AWG [1C+S(28/0.10BAS)]*3F DD:2.8/8.4 外被黑色 線芯(紅/白/黃)L:1280mm	1pc
NO	P/N	DESCRIPTION	QTY

品名	3.5四極頭+2*SR-3*RCAM 1M			
料號	HJ-230-060725-01			
製圖	ANGEL	客編:	9850-1	Y A
審核	SAM		Unit:MM	
日期	2006-08-31	Rev.:	1.00	