www.cablematic.com





Introduction

Industrial rackmount chassis is a compact 2U chasis, Cooling is essential as so many use 2U as small servers; the has 4* 8cm ball bearing cooling fans that create positive air pressure within the case. There are 2x 5.25" exposed and 6 internal 3.5" hard drive bays. The compact size, and cooling make the it as an excellent choice. The universal rear window could use Riser card or lowprofile card together

Features and Benefits

- Up to 2x 5.25" drivebay+6x3.5" HDD drivebay
- Innovation universal window for all kind of expansion!
- Front access USB2.0*2
- Standard I/O shield
- Standard PS-2 ATX





| Specification | |
|-------------------------------------|---|
| Dimension (W*H*D) | 19"*3.5"*21.65"/ 482*88.9*550(mm) |
| Material Construction | Heavy-duty and anti-rusty SECC steel,thickness:1.0mm |
| M/B Size | 12"*9.6" |
| Expansion | Universal expansion for low profile add-on card and riser card together |
| Control & Indicator | 1*Power switch +1* Reset switch |
| | 1 x LED (power) +2 x LED (HDD) |
| | 2*2.0 USB |
| Cooling Fans | 4*8cm Fan in middle |
| DriveBay | 3 x 5.25" + 1 x 3.5" (external) + 6 x 3.5" (internal) |
| Power Supply | Standard PS-2 ATX |
| | Power supply 300w~550w |
| Sliding rail | 20" ball bearing sliding rail (option) |
| Color | Black / Red / Bule / Green / Silver |
| Operation Temperature | Up to 50C (122°F) |
| Operation Humidity (Non-condensing) | Up to 90% |
| Packing Measurement CBF / CBM | 2.1 / 0.059 |
| Packing N.W / G.W | 9.0KGS /11.0KGS |