

	1	2	3	4	5	6	7	8	9	10	11	12	13	14																															
A	Art.-Nr. / Item No.		Länge / Length		VERDRAHTUNG / WIRING DIAGRAM<table><tr><th>P 1</th><th></th><th>P 2</th></tr><tr><td>1</td><td></td><td>1 WEIß / WHITE</td></tr><tr><td>2</td><td></td><td>2 ORANGE / ORANGE</td></tr><tr><td>3</td><td></td><td>3 WEIß / WHITE</td></tr><tr><td>6</td><td></td><td>6 GRÜN / GREEN</td></tr><tr><td>4</td><td></td><td>4 BLAU / BLUE</td></tr><tr><td>5</td><td></td><td>5 WEIß / WHITE</td></tr><tr><td>7</td><td></td><td>7 WEIß / WHITE</td></tr><tr><td>8</td><td></td><td>8 BRAUN / BROWN</td></tr><tr><td>SHELL</td><td></td><td>SHELL</td></tr></table>										P 1		P 2	1		1 WEIß / WHITE	2		2 ORANGE / ORANGE	3		3 WEIß / WHITE	6		6 GRÜN / GREEN	4		4 BLAU / BLUE	5		5 WEIß / WHITE	7		7 WEIß / WHITE	8		8 BRAUN / BROWN	SHELL		SHELL	A
P 1		P 2																																											
1		1 WEIß / WHITE																																											
2		2 ORANGE / ORANGE																																											
3		3 WEIß / WHITE																																											
6		6 GRÜN / GREEN																																											
4		4 BLAU / BLUE																																											
5		5 WEIß / WHITE																																											
7		7 WEIß / WHITE																																											
8		8 BRAUN / BROWN																																											
SHELL		SHELL																																											
			500±20mm																																										
			1000±20mm																																										
B			2000±30mm												B																														
			3000±50mm																																										
			5000±100mm																																										
C					CAT 6 Extension Cable, black - double-shielded LAN cable extension for connecting network components - Mounting flange with 25 mm hole spacing for fastening e.g. to a slot bracket, cable duct or enclosure - high-quality copper conductor (CU) and gold-plated contacts - S/FTP overall shield: aluminium foil shield for individual wire pairs (PiMF) and aluminium braid shield for the cable sheath - Bend protection and a sturdy jacket protect the network cable from breakage - Latch protection on the RJ45 connector prevents the latch from snagging or breaking off										C																														
D															D																														
E															E																														
F															F																														
G															G																														
H					CAT 6 Extension Cable, black - double-shielded LAN cable extension for connecting network components - Mounting flange with 25 mm hole spacing for fastening e.g. to a slot bracket, cable duct or enclosure - high-quality copper conductor (CU) and gold-plated contacts - S/FTP overall shield: aluminium foil shield for individual wire pairs (PiMF) and aluminium braid shield for the cable sheath - Bend protection and a sturdy jacket protect the network cable from breakage - Latch protection on the RJ45 connector prevents the latch from snagging or breaking off										H																														
I	Änderungen				Datum		Name		Bezeichnung						Blatt		I																												
	Datum		Name		gez.:	22.09.2023	alw	CAT 6-XXXX S/FTP EXTENSION/ mounting X,XM						1/2																															
	22.07.2024		fw		gepr.:	22.09.2023	alw																																						
					Norm:			Zeichnungs-Nr.:						von		J																													
J					Änderungen vorbehalten / Subject to change																																								
	1	2	3	4	5	6	7	8	9	10	11	12	13	14																															

