











USB3.0 BM		USB3.0 BM
1	——	1
2	——	2
3	——	3
4	——	4
5	——	5
6	——	6
7	——	7
8	——	8
9	——	9
SHELL	——	SHELL

ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance:10ohm
3. Insulation Resistance:5Mega ohm
4. Hipot test:300V/10ms

NO.	DESCRIPTION	Q'TY	UNIT
4	55P PVC MOLDING BLUE IN COLOR		
3	USB3.0 B TYPE MALE SOLDER SHELL PLATED:NICKEL CONTACT:30U"	1	pcs
2	USB3.0 B TYPE MALE SOLDER SHELL PLATED:NICKEL CONTACT:30U"	1	pcs
1	INTERNAL WIRES;UL1007 30AWG		

REV.	DESCRIPTION	DATE
A		10/09/23

UNLESS OTHERWISE SPECIFIED TOLERANCE
ANG. ±5'
0. ±0.5
.0 ±0.3
.00 ±0.2

SCALE: NONE	UNIT: mm		
DRAWN Steven	10/09/23	DRAWN NAME:	競捷-UY04
CHECKED eric	10/09/23		
APPROVED		PRODUCT NO.	
	SIZE A4	REV. A	FILE NAME: